




技術資料 Technical data

- 開機即用,免開發程式
- 多國語言設定與顯示
- 運轉中可快速編輯程式參數並儲存
- 整機IP66保護,應用面更廣
- 多樣性顯示圖案,跑馬燈,長條圖,指示燈....
- 具外部功能鍵與同時雙畫面顯示
- 具數位示波器功能可同時追蹤多組類比數值
- 支援開機畫面設定
- 標準2.4GHz IEEE 802.11 b/g (Wi-Fi),各國都可使用
- 螢幕解析度:96x 64 像素
- 雙看門狗計時器
- 遙控器可直接設定多種特殊功能設定,無須PC軟體
- 資料傳送WPA2-PSK (AES)加密,防護嚴密
- 可7組獨立遙控器同時對應單一組控制器,同時執行不同操作
雙向通訊,可由遙控器的顯示屏了解即時狀況
- 可多頻道多分群同時使用,無一般ID組數限制
- 可調整Wi-Fi發射功率
- Plug & Play Directly
- Multi-Lingual Display Menu
- Able To Edit The Parameter Among The Controller Operation
- IP66 Protection
- Display Text Display Diversity Patterns, Scrolling Text, Bar Charts, Indicators
- Built-in Function Key & Twin Display
Digital Oscilloscope Function, Real-Time Monitoring
- Support Start-Up display
- Standard 2.4GHz IEEE 802.11 b/g (Wi-Fi)
- Display Resolution: 96*64 pixels
- Dual Watchdog Timer
- The Transmitter able to edit controller program /parameter directly without PC software
- Support WPA2-PSK(AES)
- Able to use 7 units Transmitter to communicate
with 1 unit Wi-Fi controller, and process the Independent operation per Transmitter
- Two-Way communicate system, can via the display to monitor
- Multi-Channel & Multi-Clustering can be used simultaneously, no ID groups limit
- Adjustable transmission power

型號Type	EAC-C (Wi-Fi 雙向通訊遙控器)	
工作電壓	Operation Voltage	AA電池 * 4 / RCR-V3
顯示屏	Display	1.8 " STN 液晶屏
對比度	Contrast	直接調整Adjustable directly
分辨率	Resolution	96*64 像素pixels
液晶屏壽命	STN Display Life	50000小時以上More than 50000 hours
亮度	Brightness	60cd/m2
色彩	Display color	單色Monochrome
功能按鍵	Function keys	9個可自由定義9, Definable
顯示尺寸	Display Dimension	38*28 mm
操作溫度	Operation Temperature	-20 TO +75°C
防護等級	Degree of Protection	IP66
通訊規格	Communication	標準Standard2.4GHz IEEE 802.11 b/g (Wi-Fi)
尺寸(W x H xD) Dimension		222.1*65.6*45 mm

訂購代號 How to code

EAC-C

單一機種